ProLite C270WT | 68 cm

Innovation in the world of home TV! ProLite C270WT offers pure enjoyment in viewing TV or video/DVD on its 27" (68 cm) 16:9 screen! Resolution of 1280 x 720 pixels along with high contrast (500:1) and excellent brightness (500 cd/m2) guarantee the best image quality. The PIP function, 8-watt stereo speakers and functional remote control complement the already rich list of features. All this at an excellent value for the dollar typical of iiyama.

Technical data

Panel	WideScreen
Diagonal	68 cm (27")
Display area h x w	335,9 x 597 mm
Contrast ratio	500 : 1 typical
Brightness	500 cd / m² typical
Response time	16 (gray-white-gray) msec
Viewing zone	horizontal/vertical: 170°/170°; right/left 85°/85°, up/down: 85°/85°
Display colour	16,7 Million
Pixel pitch h x v	0,4665 x 0,4665 mm
TV-Standard	PAL (BG/DK/I), SECAM, NTSC, HDTV (480i, 480)
Sound	stereo, 2-channel
Inputs	Euro-Scart, Video, S-Video, Component Video (YPbPr, audio P/L), antenna (analog), audio output (P/L, subwoofer)
Channels programming TV/AV	99
Teletext	Simple-Text, TOP-Text Fast-Text
PIP (Picture in Picture)	PC/TV, PC/Video, Video/YpbPr (adjustable: position, size and video source for the PIP window)
Picture formats	16:9, 4:3, Panoramic
Remote control	IR remote control, OSD (On Screen Display)
TV equipment	automatic station programming, simple channel sorting
Horizontal sync	31 - 65 KHz
Vertical sync	50 - 85 Hz
Bandwith	108 MHz
Native resolution	0,92 Mpix (1280 x 720)
Input connector	D-Sub 15 mini
Syncronisation	Separate-Sync.
Plug and Play	DDC 1/2B™
Speaker	2 x 8 W stereo
Included accessories	IR remote control (+ batteries), analog VGA signal cable, audio cable (PC), user manual, Info CD
User controls	brightness, contrast, colour temperature (3 presets, one user predefined setting, separate RGB adjustments), white balance, colour, hue, sharpness, audio settings (volume, bass, treble, virtual sound, balance), vertical and horizontal image position, timing, phase, signal input, OSD position, reset, PIP (PIP window size, position and signal source), automatic channel search, channel adjustments
Driver	Windows 95 / 98 / 2000 / ME / XP
Safety	CE, CB, CUL/UL, BSMI, FCC Class C, VCCI
Power supply	AC 100 - 240 V, 50 / 60 Hz
power supply	internal
Power usage	max. 150 W during operation, max. 15 W during stand-by
Power management	VESA DPMS, ENERGY STAR®, tryb ECO
Dimensions w x h x d	830 x 480 x 150 mm
Weight	23,8 with stand kg

All trademarks and registered trademarks acknowledged. E & O E. Specifications subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defaults.